



1525-BRS

BRUSH SERVO MOTOR DRIVE



Performance Characteristics

Peak Power	4.1 kW
Peak Output Voltage	± 164 VDC (shut off @ 205 VDC)
Peak Output Current	± 25 amps (1 sec.)
Max. Continuous Current	± 15 amps (50 °C), ± 19 amps (25 °C)
Internal Shunt Regulator	55 W continuous, 2.4 kW peak for .02 seconds (activates at 190 VDC)

Electrical Characteristics

Input Signal Voltage	± 10 VDC (typ.), ± 35 VDC (max.)
System Gain	0 to 10,000 amps/volt – velocity mode 0 to 10.0 amps/volt – torque mode
Input Impedance	40 k Ohms
Typical Input Drift	10 µV/°C
Bandwidth	2 kHz with 1.2 mH Inductance
Dead Band	Zero

Input Power Requirements

Input Voltage	45-120 vac
---------------	------------

Adjustments

Peak Current Limit	0 to 25 amps
RMS Current Limit	0 to 19 amps
Signal Command Input	Scaling
Balance	Zero velocity offset
Compensation	System response
Tachometer	Scaling

Diagnostics

Bus Over Voltage	Red LED
Excessive RMS/Over Temp.	Red LED
Surge/Ground Fault	Red LED
Amplifier Operational	Green LED

Physical Characteristics

Module Dimensions (l x w x h)	7.6 in. x 2.5 in. x 4.7 in.
Weight	2.4 lbs
Ambient Temperature	0 °C to 50 °C
Shutdown Temperature	80 °C at heat sink
Relative Humidity	5 - 95% non-condensing